

32E: Colton-Duxbury complex, 25 to 60 percent slopes

The Colton component makes up 45 percent of the map unit. The natural drainage class is excessively drained. Water movement in the most restrictive layer is high. This component is on outwash terraces. The parent material consists of sandy and gravelly glaciofluvial deposits. Depth to a root restrictive layer is greater than 60 inches.

The Duxbury component makes up 35 percent of the map unit. The natural drainage class is well drained. Water movement in the most restrictive layer is high. This component is on outwash terraces. The parent material consists of sandy and gravelly glaciofluvial deposits. Depth to a root restrictive layer is greater than 60 inches.

Vermont Residential Onsite Waste Disposal Group and Subgroup: Ile

This unit is moderately suited as a site for soil-based residential wastewater disposal systems, based on a review by the Natural Resources Conservation Service of criteria set forth in the Vermont 2007 Environmental Protection Rules. The rapid permeability in the substratum and slopes greater than 20 percent are the primary concerns. Backfilling absorption trenches and beds with at least one foot of finer textured material, or other site modifications, may be necessary to slow the percolation rate enough to allow for thorough filtering of effluent. Cut and fill site modifications may produce an acceptable area within the unit. An erosion prevention and sediment control plan is required by the State for construction on sites over 20 percent slope.

PHYSICAL and CHEMICAL PROPERTIES								EDOSION EACTORS	
Soil name	Depth	Typical texture	Clay (Pct)	Soil reaction (pH)	Permeability (In/Hr)	Organic matter (Pct)	EROSION FACTORS		
	(ln)						Kw	Kf	Т
Colton	0-1	SPM		3.5 - 5.5	2-6	35-100			5
	1-9	FSL	0-7	3.5 - 6.0	2-100	1.0-5.0	.24	.24	
	9-13	GRV-LS	0-7	3.5 - 6.0	2-100	1.0-4.6	.10	.24	
	13-22	GR-COS	0-5	3.5 - 6.0	2-100	0.5-3.0	.02	.02	
	22-65	GRV-COS	0-3	4.5 - 6.5	20-100	0.0-0.5	.02	.02	
Duxbury	0-2	MPM		3.5 - 5.5	2-6	35-100			3
	2-16	FSL	0-7	3.5 - 6.5	2-6	1.0-5.0	.32	.32	
	16-28	GR-LFS	0-7	3.5 - 6.5	2-6	0.5-2.5	.20	.37	
	28-65	GRV-S	0-5	4.5 - 6.5	6-100	0.0-0.5	.02	.02	

WATER FEATURES							SOIL FEATURES		
	Hydrologic	Depth to seasonal		ding	Ponding		Hydric		
Soil name	group	high water table (Feet)	Frequency	Duration	Frequency	Duration	soil?	Depth to bedrock (range in inches)	
Colton	Α		None		None		No		
Duxbury	Α		None		None		No		

LAND USE LIMITAT	<u>AGRICULTUR</u>	AGRICULTURAL YIELD DATA				
Land use	Rating	Reason **	Crop name	Yield / acre		
Dwellings with basements:	Very limited	Slope	•			
Dwellings with basements:	Very limited	Slope				
Pond reservoir areas:	Very limited	Seepage				
Pond reservoir areas:	Very limited	Seepage				
	Land use Dwellings with basements: Dwellings with basements: Pond reservoir areas:	Dwellings with basements: Very limited Dwellings with basements: Very limited Pond reservoir areas: Very limited	Land use Rating Reason ** Dwellings with basements: Very limited Slope Dwellings with basements: Very limited Slope Pond reservoir areas: Very limited Seepage	Land use Rating Reason ** Crop name Dwellings with basements: Very limited Slope Dwellings with basements: Very limited Slope Pond reservoir areas: Very limited Seepage		

	Management	WOODLAND MANAGEMENT					
Soil name	concern	Rating	Reason	Vermont natural communities			
Colton	Harvest equip operability:	Poorly suited	Slope	Hemlock-Northern Hardwood Forest,			
Duxbury	Harvest equip operability:	Poorly suited	Slope	Hemlock-White Pine-Northern Hardwood Forest Variant.			
Colton	Road suitability:	Poorly suited	Slope	Lowland Spruce-Fir Forest, well drained phase,			
Duxbury	oury Road suitability:		Slope	White Pine-Northern Hardwood Forest Variant, Hemlock Forest.			
Colton	Erosion hazard (off-road):	Severe	Slope/erodibility	Red Pine Forest or Woodland			

Soil Fact Sheet - Continued

Caledonia County, Vermont

Duxbury

Erosion hazard (off-road): Severe

Slope/erodibility