

MuD: Munson and Belgrade silt loams, 12 to 25 percent slopes

The Belgrade component makes up 43 percent of the map unit. The natural drainage class is moderately well drained. Water movement in the most restrictive layer is moderately low. This component is on terraces on lake plains. The parent material consists of coarse-silty glaciolacustrine deposits. Depth to a root restrictive layer is greater than 60 inches.

The Munson component makes up 43 percent of the map unit. The natural drainage class is somewhat poorly drained. Water movement in the most restrictive layer is very low. This component is on terraces on lake plains. The parent material consists of coarse-silty glaciolacustrine deposits over clayey glaciolacustrine deposits. Depth to a root restrictive layer is greater than 60 inches.

Important farmland classification: NPSL	Land capability: 4 e	Vermont Agricultural Value Group: 8d
---	----------------------	--------------------------------------

Vermont Residential Onsite Waste Disposal Group and Subgroup: Ille


This unit is marginally suited as a site for soil-based residential wastewater disposal systems, based on a review by the Natural Resources Conservation Service of criteria set forth in the Vermont 2007 Environmental Protection Rules. The depth to the seasonal high water table and slopes greater than 20 percent in some areas are the major limitations. A detailed, site-specific analysis is generally required. On-site groundwater level monitoring and determination of induced groundwater mounding is often necessary to establish the suitability of this unit. Curtain drains may help lower the water table to an acceptable level. There may be less-sloping areas within the unit that are suitable for siting a septic system, or, if feasible, cut and fill site modifications may produce an acceptable area within the unit. An erosion prevention and sediment control plan is required by the State for construction on sites over 20 percent slope.

	PHYSICAL and CHEMICAL PROPERTIES EROSION FACTORS				CTORS				
Soil name Depth		Typical	Clay	Soil reaction	Permeability (In/Hr)	Organic	EROSION FACTORS		
Sui name	(ln)	texture	(Pcť)	(pH)	(111/111)	matter (Pct)	Kw	Kf	Т
Belgrade	0-7	VFSL	4-15	4.5 - 7.3	0.6-2	1.0-5.0	.32	.32	5
	7-23	VFSL	4-15	4.5 - 7.3	0.6-2	0.5-3.0	.49	.49	
	23-60	VFSL	2-20	6.1 - 7.8	0.06-6	0.0-1.0	.55	.55	
Munson	0-8	SIL	3-10	5.6 - 6.5	0.6-2	3.0-10	.49	.49	3
	8-15	SIL	3-16	5.6 - 6.5	0.2-2	0.5-3.0	.64	.64	
	15-65	SIC	35-60	5.6 - 7.3	0-0.2	0.0-1.0	.32	.32	

<u>WATER FEATURES</u>						SOIL FEATURES		
	Hydrologic	Depth to seasonal	Flooding		Ponding		Hydric	
Soil name	group	high water table (Feet)	Frequency	Duration	Frequency	Duration	soil?	Depth to bedrock (range in inches)
Belgrade	B/D	1.5-3.5	None		None		No	
Munson	C/D	0.5-2.0	None		None		No	

	LAND USE LIMITA	AGRICULTURAL YIELD DATA			
Soil name	Land use	Rating	Reason **	Crop name	Yield / acre
Munson	Dwellings with basements:	Very limited	Depth to saturated zone	Grass-legume hay	3 Tons
Belgrade	Dwellings with basements:	Very limited	Depth to saturated zone	Corn silage	18 Tons
Munson	Dond reconscir ereces	Very limited	Slope	Alfalfa hay	3.5 Tons
	Pond reservoir areas:	,	•	Pasture	7 AUM
Belgrade	Pond reservoir areas:	Very limited	Slope	Grass-clover	5.2 AUM

	Management	WOODLAND MANAGEMENT					
Soil name	concern	Rating	Reason	Vermont natural communities			
Munson	Harvest equip operability:	Poorly suited	<30cm to water table for >=6mos	Valley Clayplain Forest			
Belgrade	Harvest equip operability:	Moderately suited	30-60cm to water table t				
Munson	Road suitability:	Poorly suited	Slope				
Belgrade	Road suitability:	Poorly suited	Slope				



Soil Fact Sheet - Continued

Chittenden County, Vermont

Munson Erosion hazard (off-road): Moderate Slope/erodibility
Belgrade Erosion hazard (off-road): Moderate Slope/erodibility