

67D: Georgia and Amenia soils, 15 to 25 percent slopes, very stony

The Amenia component makes up 40 percent of the map unit. The natural drainage class is moderately well drained. Water movement in the most restrictive layer is moderately low. This component is on hills on glaciated uplands, ridges on glaciated uplands. The parent material consists of coarse-loamy till. Depth to a root restrictive layer is greater than 60 inches.

The Georgia component makes up 40 percent of the map unit. The natural drainage class is moderately well drained. Water movement in the most restrictive layer is moderately low. This component is on hills on glaciated uplands, ridges on glaciated uplands. The parent material consists of coarse-loamy till. Depth to a root restrictive layer is greater than 60 inches.

Important farmland classification: NPSL	Land capability: 6 s	Vermont Agricultural Value Group: 10
---	----------------------	--------------------------------------

Vermont Residential Onsite Waste Disposal Group and Subgroup: IIIe

This unit is marginally suited as a site for soil-based residential wastewater disposal systems, based on a review by the Natural Resources Conservation Service of criteria set forth in the Vermont 2007 Environmental Protection Rules. The depth to the seasonal high water table and slopes greater than 20 percent in some areas are the major limitations. A detailed, site-specific analysis is generally required. On-site groundwater level monitoring and determination of induced groundwater mounding is often necessary to establish the suitability of this unit. Curtain drains may help lower the water table to an acceptable level. There may be less-sloping areas within the unit that are suitable for siting a septic system, or, if feasible, cut and fill site modifications may produce an acceptable area within the unit. An erosion prevention and sediment control plan is required by the State for construction on sites over 20 percent slope.

PHYSICAL and CHEMICAL PROPERTIES EROSION FACTORS									
0.1	Depth	Typical	Clay	Soil	Permeability (In/Hr)	Organic	EROSION FACTORS		
Soil name Deptit Typical Clay reaction (Pct) (pH)			(In/Hr) matter (Pct)		Kw	Kf	Т		
Amenia	0-8	L	5-18	5.6 - 7.3	0.6-2	2.0-6.0	.28	.28	3
	8-24	GR-L	5-18	5.6 - 7.3	0.6-2	0.5-2.0	.28	.49	
	24-60	GR-FSL	5-18	7.4 - 8.4	0.06-0.2	0.0-0.5	.24	.37	
Georgia	0-8	L	7-18	5.1 - 7.3	0.6-2	3.0-8.0	.28	.28	3
	8-30	GR-L	5-18	5.1 - 7.3	0.6-2	0.0-1.0	.28	.43	
	30-60	GR-L	10-18	5.1 - 7.3	0.06-0.2	0.0-0.5	.28	.49	

		WATE	R FEATURES				SOIL	<u> FEATURES</u>
	Hydrologic	Depth to seasonal	Floo	ding	Pon	ding	Hydric	
Soil name	group	high water table (Feet)	Frequency	Duration	Frequency	Duration	soil?	Depth to bedrock (range in inches)
Amenia	С	1.5-3.0	None		None		No	
Georgia	С	1.5-3.0	None		None		No	

	LAND USE LIMITA	<u> </u>		AGRICULTURA	L YIELD DATA	
Soil name	Land use	Rating	Reason **	Crop name	Yield / acre	
Georgia	Dwellings with basements:	Very limited	Slope	Pasture	3 AUM	
Amenia	Dwellings with basements:	Very limited	Slope	Pasture	3.8 AUM	
Georgia	Pond reservoir areas:	Very limited	Slope			
Amenia	Pond reservoir areas:	Very limited	Slope			

	Management	<u>v</u>	OODLAND MANAGE	<u>EMENT</u>
Soil name	concern	Rating	Reason	Vermont natural communities
Georgia	Harvest equip operability:	Moderately suited	Slope	Mesic Maple-Ash-Hickory-Oak Forest,
Amenia	Harvest equip operability:	Moderately suited	Slope	Rich Northern Hardwood Forest, Sugar Maple-White Ash Northern Hardwood
Georgia	Road suitability:	Poorly suited	Slope	Forest
Amenia	Road suitability:	Poorly suited	Slope	
Georgia	Erosion hazard (off-road):	Moderate	Slope/erodibility	
Amenia	Erosion hazard (off-road):	Moderate	Slope/erodibility	

