

705D. Rawsonville-Houghtonville association, hilly, rocky

The Rawsonville component makes up 55 percent of the map unit. The natural drainage class is well drained. Water movement in the most restrictive layer is low. This component is on hills on glaciated uplands, mountains on glaciated uplands. The parent material consists of coarse-loamy till. Depth to a root restrictive layer, bedrock, lithic, is 20 to 40 inches.

The Houghtonville component makes up 30 percent of the map unit. The natural drainage class is well drained. Water movement in the most restrictive layer is moderately high. This component is on hills on glaciated uplands, mountains on glaciated uplands. The parent material consists of coarse-loamy till. Depth to a root restrictive layer is greater than 60 inches.

Important farmland classification: NPSL	Land capability: 6 s	Vermont Agricultural Value Group: 10
---	----------------------	--------------------------------------

Vermont Residential Onsite Waste Disposal Group and Subgroup: IId

This unit is moderately suited as a site for soil-based residential wastewater disposal systems, based on a review by the Natural Resources Conservation Service of criteria set forth in the Vermont 2007 Environmental Protection Rules. The depth to bedrock and slopes greater than 20 percent in some areas are the primary concerns. A significant percentage of this map unit has sufficient soil depth over bedrock to accept a range of designs. On-site investigations can help avoid areas with limited depth to bedrock. Additional fill material may be needed in some areas in order to meet the separation distance requirement between the bottom of the leachfield and bedrock. There may be less-sloping areas within the unit that are suitable for siting a septic system, or, if feasible, cut and fill site modifications may produce an acceptable area within the unit. An erosion prevention and sediment control plan is required by the State for construction on sites over 20 percent slope.

PHYSICAL and CHEMICAL PROPERTIES						EROSION FACTORS			
Soil name	I Donth I Typical I Clay I	Permeability (In/Hr)	Organic matter	EROSION FACTORS					
Soli Harrie	(ln)	texture	(Pct)	(pH)	(117111)	(Pct)	Kw	Kf	Т
Rawsonville	0-3	GR-FSL	3-10	3.6 - 5.5	0.6-6	4.0-8.0	.10	.24	2
	3-23	GR-FSL	3-10	3.6 - 5.5	0.6-6	2.0-8.0	.17	.28	
	23-30	GR-SL	3-10	3.6 - 5.5	0.6-6	2.0-6.0	.15	.32	
	30-40	UWB			0.01-20				
Houghtonville	0-2	GR-FSL	3-10	3.6 - 6.0	0.6-6	4.0-8.0	.10	.17	5
	2-29	GR-FSL	3-10	3.6 - 6.0	0.6-6	2.0-6.0	.17	.28	
	29-60	GR-FSL	3-10	3.6 - 6.0	0.6-6	0.5-2.0	.17	.32	

		WATE	R FEATURES				SOIL	FEATURES	
	Hydrologic	Depth to seasonal	Flooding		Ponding		Hydric		
Soil name	group	high water table (Feet)	Frequency	Duration	Frequency	Duration	soil?	Depth to bedrock (range in inches)	
Rawsonville	С		None		None		No	20-40	
Houghtonville	В		None		None		No		

	LAND USE LIMITA	<u>TIONS</u>		AGRICULTURA	L YIELD DATA
Soil name	Land use	Rating	Reason **	Crop name	Yield / acre
Rawsonville Houghtonville	Dwellings with basements: Dwellings with basements:	•	Depth to hard bedrock Slope		
Rawsonville Houghtonville	Pond reservoir areas: Pond reservoir areas:	Very limited Very limited	Slope Slope		

	Management	WOODLAND MANAGEMENT				
Soil name	concern	Rating	Reason	Vermont natural communities		
Rawsonville	Harvest equip operability:	Moderately suited	Slope	Montane Yellow Birch-Red Spruce Forest,		
Houghtonville	Harvest equip operability:	Moderately suited	Slope	Red Spruce-Northern Hardwood Forest, Northern Hardwood Forest		
Rawsonville	Road suitability:	Poorly suited	Slope	Notifielli Hardwood Polest		
Houghtonville	Road suitability:	Poorly suited	Slope			
Rawsonville	Erosion hazard (off-road):	Moderate	Slope/erodibility			



Soil Fact Sheet - Continued

Rutland County, Vermont

Houghtonville

Erosion hazard (off-road): Moderate

Slope/erodibility