

80D: Macomber-Taconic complex, 15 to 25 percent slopes, very rocky

The Macomber, very rocky component makes up 55 percent of the map unit. The natural drainage class is well drained. Water movement in the most restrictive layer is low. This component is on moderately steep hills on glaciated uplands. The parent material consists of loamy till. Depth to a root restrictive layer, bedrock, lithic, is 20 to 40 inches.

The Taconic, very rocky component makes up 30 percent of the map unit. The natural drainage class is somewhat excessively drained. Water movement in the most restrictive layer is low. This component is on moderately steep hills on glaciated uplands. The parent material consists of loamy till. Depth to a root restrictive layer, bedrock, lithic, is 10 to 20 inches.

Important farmland classification: NPSL	Land capability: 6 s	Vermont Agricultural Value Group: 10
---	----------------------	--------------------------------------

Vermont Residential Onsite Waste Disposal Group and Subgroup: Ild

This unit is moderately suited as a site for soil-based residential wastewater disposal systems, based on a review by the Natural Resources Conservation Service of criteria set forth in the Vermont 2007 Environmental Protection Rules. The depth to bedrock and slopes greater than 20 percent in some areas are the primary concerns. A significant percentage of this map unit has sufficient soil depth over bedrock to accept a range of designs. On-site investigations can help avoid areas with limited depth to bedrock. Additional fill material may be needed in some areas in order to meet the separation distance requirement between the bottom of the leachfield and bedrock. There may be less-sloping areas within the unit that are suitable for siting a septic system, or, if feasible, cut and fill site modifications may produce an acceptable area within the unit. An erosion prevention and sediment control plan is required by the State for construction on sites over 20 percent slope.

PHYSICAL and CHEMICAL PROPERTIES								EDOCION FACTORS	
Soil name	Depth	Typical	Clay	Soil reaction (pH)	Permeability (In/Hr)	Organic matter (Pct)	EROSION FACTORS		
	(In)	texture	(Pct)				Kw	Kf	Т
Macomber, very rocky	0-3	MPM		3.2 - 5.7	2-6	25-100			2
	3-7	SIL	10-27	4.5 - 5.5	0.6-2	2.0-6.0	.28	.28	
	7-33	CNV-SIL	10-27	4.5 - 5.5	0.6-2	0.0-1.0	.15	.49	
	33-43	UWB			0.01-20				
Taconic, very rocky	0-3	MPM		3.2 - 5.7	2-6	25-100			1
	3-6	CN-SIL	10-27	4.5 - 5.5	0.6-6	2.0-6.0	.20	.37	
	6-15	CNV-SIL	10-27	4.5 - 5.5	0.6-6	0.0-1.0	.20	.49	
	15-25	UWB			0.01-20				

WATER FEATURES								SOIL FEATURES		
	Hydrologic	Depth to seasonal	Flooding		Ponding		Hydric			
Soil name	group	high water table (Feet)	Frequency	Duration	Frequency	Duration	soil?	Depth to bedrock (range in inches)		
Macomber, very rocky	С		None		None		No	20-40		
Taconic, very rocky	D		None		None		No	10-20		

	LAND USE LIMITA	AGRICULTU	AGRICULTURAL YIELD DATA			
Soil name	Land use	Rating	Reason **	Crop name	Yield / acre	
Macomber, very rocky	Dwellings with basements:	Very limited	Slope	Pasture Pasture	2.7 AUM 1.7 AUM	
Taconic, very rocky	Dwellings with basements:	Very limited	Slope	•		
Macomber, very rocky	Pond reservoir areas:	Very limited	Slope			
Taconic, very rocky	Pond reservoir areas:	Very limited	Slope			

	Management	<u>v</u>	OODLAND MAI	NAGEMENT .
Soil name	concern	Rating	Reason	Vermont natural communities
Macomber	Harvest equip operability:	Moderately suited	Slope	Northern Hardwood Forest,
Taconic	Harvest equip operability:	Moderately suited	Slope	Mesic Red Oak-Northern Hardwood Forest, Dry Oak-Hickory-Hophornbeam Forest,
Macomber	Road suitability:	Poorly suited	Slope	Red Cedar Woodland, Mesic Maple-Ash-Hickory-Oak Forest,



Soil Fact Sheet - Continued

Windsor County, Vermont

Taconic Slope Road suitability: Poorly suited Macomber

Erosion hazard (off-road): Moderate Slope/erodibility Taconic Erosion hazard (off-road): Moderate Slope/erodibility Temperate Acidic Outcrop, Temperate Acidic Cliff